Zigpac

Contact Methods
Mob: (86)18668768846
Tel: (86) 577 68668118
Wechat: zigpac123
Skype: bruce.chan1999
E-mail: bruce@zigpac.com
Whatsapp: +86-18668768846
Telegram: @Zigpacstickers

Company Info
Name: Wenzhou Zigpac Industry Limited
Address: No. 148-152, Building C, Jiangbin Commercial and Residential Building, Longgang City, Wenzhou City, Zhejiang 325802, China

YOUR CUSTOM

PRINTING & PACKAGING **PARTNER** FOR SMALL AND **MEDIUM BUSINESSES**

□□□□□□□□□□□□□□□□□□□□□□□□□□

Product Image

WANDER
MORE
EXPLORE
MORE
LIFE IS BETTER
AROUND THE FIRE
Adventure Awaits

EXPLORE
MORE
ROUND THE
Adv

WANDER
MORE
EXPLORE
MORE
LIFE IS BETTER
AROUND THE FIRE
EXPLORE
MORE
Adventure Awaits

WANDER
MORE
WANDER
MORE
N
W
E
EXPLORE
MORE
LIFE IS BETTER
AROUND THE FIRE
LIFE IS BETTER
AROUND THE FIRE
Adventure Awaits

Details

[illegible] **UV DTF** [illegible]

[illegible] PrintRunner [illegible][1][illegible]

[illegible] “[illegible]” [illegible] Decals.com [illegible] “[illegible]” [illegible] “[illegible]” [illegible][4]. [illegible]

□□

- □□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□□□□
- □□□□□□□□□□□□□
- □□□□□□□□□□□□□□□
- □□□□□□□□□□□□□□□
- □□□□□□□□□□□□
- □□□□□□□□□□
- □□□□□□□□□□□□□□
- □□□□
- □□□□□□□□□□□□□□

□□□□□□□□□□□□□□ ↑

□□□□□□□□3□□□□□□□□□□□□□□□□□□□□□□□□□□□□Want Stickers □□□□□□□□□“□□□□□□□□□□□□□□□□□□□‘□□’□□□□□”□□□□□□□ □□□□□□[5]□□□□□□□□□□□□□□□□□□□□□□□□4over4 □□□□“□□□”□□□□ □□□□□□[6]□□

□□	□□	□□□□□	□□□□	□□□□
□□□□□□□□□□□□	□□□□□□□□□□□□□□□□□□	□□□□□□□□□□□□	□□□□□□	□□□□□□□□□□□□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□	□□□□□□□□	□□	□□□□□□□□□□□□□□□
UV DTF □□	□□□□□□□□□□□□	□□□□□□□	□□□□□□□□	□□□□□□□□□□□□□□
□□□□□□□□□□	□□□□□□□□□□□□□	□□□□□□	□□□□□	□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□Sticker Mule □ □□□□□□[7] □□□□□□□□□□□ 3.4 mil□86 µm□□□□□□□□□□□“□□□□□□”□□□□□□□□□ UV □□□UV DTF □□□□□□□□□□The Print Reviewer □□ UV DTF □□□□□□[8].

□□□□□□□□□□□□□□□□□□□□ ↑

□□Sticker Mule □ □□□□□□□[9] □□□□□□□□□0.08 in□□□□□□□□0.09 in□□□□□1 × 1 in□15 × 15 in□□□□□□□□□300 PPI□□□Decals.com □ □□□□□[10] □□□□□□□□□□□□□□□□□□□□□□1/2 in□□□□□1/8 in□□

YG Tape □□ □□□□□□□□[11]□□□□“□□□□□□□□□□□□□□□□□□□□□□□□□□□□□”□□□□□□□□□□□ a□e□o □□

□□□□□□□□□□□□□□□□□□□□□□ ↑

□□□□□□□□□□□□□Stickerit □ □□□□□□[12] □□□“□□□□□”□□□□□□□□ 30 □□□□□□□□□□□□□□□□□Kim's Direct □□ □□□□□□□[13]□□“□□□□□□□□□□□□□□□”□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□HDPE □ PP □□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□Flywheel Brands □□ □□□□□□□[14]:

□□□□	□□□□□□□□□□□	□□
□□□□□□□□	□□□ 1 □□□□	Flywheel Brands □□
□□□□□□	5–7 □	Flywheel Brands □□
□□□□□□	8–10 □	Flywheel Brands □□
□□□□□ + □ UV □□	□ 8 □□□□ 3M □□□	Flywheel Brands □□
Avery MPI 1105 SuperCast□□□□	□□ 7 □	Avery PDS□□□□ 12

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□Flywheel □□□□Avery Dennison □□□□□□□□□□□□□□□□50%□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□Avery □ MPI 1105 □□□[15] □□□□□□12/15/25□□□□□□□□□□□□□□□□45°F□□□□□50°F□□□□□60°F□□

[illegible] ↑

[illegible]Stickerit [illegible] AI[illegible]EPS[illegible]SVG [illegible] PDF[illegible] JPG [illegible] PNG[illegible]

- [illegible]
- [illegible]
- [illegible]
- [illegible]
- [illegible]

[illegible]

[illegible] ↑

[illegible]

[illegible] 0.5–1 in [illegible]PalmGear [illegible][16][illegible]“[illegible]”[illegible] Oracal[illegible]Cricut [illegible] Siser [illegible]

□□□□□□□□□□□□□□□ ↑

□□□□□□□□□□□□□□“□□”□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□	□□□□	□□□□
□□□□□□□	□□□□□□□□□□□□	□□□□□□□□□□□
□□□□□□□□□□□□□□□	□□□□□□□□□□□□	□□□□□□□□□□□□□
□□□□□□□□□□□□	□□□□□□□□□□□□□□□□	□□□□□□□□□□□□□□
□□□□□□□□□	□□□□□□□□□□□□□	□ mm □□□□□□□□□
□□□□□□	□□□□□□□□□□	□□□□□□□□

□□□ FINAT □□□□[17] □□FTM 1□180° □□□□□□□300 mm/□□□□FTM 9□□□□□□□FTM 14□□□□□□□□□□□□□□□ASTM G155□□□□□□□□ Brady □ □□□□□□□[18] □□

□□□□□□□□□□□□ ↑

□□□□□□□□□□□□□□□□□□□□□□□□□□□

- □□□□□□□□□□□□□□□Printable Press □□ □□□□[19]□□“70% □□□□□”□□□□“□□□□□□□□□”□□□□□□□□□□□□□□□
- □□□□□Vinyl Status □□ □□□□[20]□□□□“□□□□ 50°F□10°C□”□Decals.com □□□□□□□□□□□ 60–80°F□
- □□□□□□□□□□□□□□□□□□□□□□□□□□□□
- □□ 45° □□□□□□□□□□□□□□□□□□□□□
- □□□ 180° □□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 24–48 □□□□□□□

□□□□□□□Sticker Mule □□□□□□□□□□□□□□□□ 24 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□ ↑

□□□□□□□□□□□□□□□□

□□□□□	□□□	□□□□
□□□□□□□□□□□□□□□□	□□□□□□□	□□□□□□□□□□
□□□□□□□□□□□□	□□□□□□	□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□	UV DTF	□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□	□□□□□□□□□	□□□□□□
□□□□□ UV □□	□□□□□	□□□□□□□□□□□

□□PrintRunner □□2 mil □□□□□□□□□□□□□“□□□□□□□□□□”□□□

□□□□□□□□□□□□□□□□UL 969 □□□□□□□□□□□□□□□□□□□□□□□□ UL 969 □□□□[22]□□□□□□□□□□□CPSC □ □□□□□□□□[23]□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 0.1%□1,000 ppm□□□□□□□□ 12 □□□□□□□□□□□□□□□□□□□OEHHA □□□S □□□ 65 □□□[24]□□□□□□ 2024-12-29 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□FINAT □ PFAS □□[25] □□□PPWR □□□ 2026-08-12 □□□□□□□□□□□□□□□□□□□□□□□□□□□□ PVC □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□ ↑

□□□Avery □□□□□□□□□□□□□□□□2□□□□□□□□□□□□□□□□□□□□□□□□

□□

买家要点 ↑

纯色刻字转印适合干净、光滑的户外表面，可使用数年而非数十年 ——在出现明显褪色前为 3 to 5 年（来源)
水平面会大幅缩短膜材额定寿命 ——按 Avery Dennison 保证条款减少 50%（来源)
低温表面会减慢胶黏剂润湿 ——最低表面温度 50°F（10°C）（来源)
图稿定稿前，细线条需满足公开最低限值 ——某主流印刷商要求实心部分 0.08 in、间隙 0.09 in（来源)
CPSIA 邻苯二甲酸酯限值仅适用于儿童玩具和护理用品 ——0.1%（1,000 ppm）（来源)
第三方贴纸市场估算采用不同口径，不应相加 ——贴纸子市场 $1.60 十亿（2024），预计到 2030, 10.4% 年以 $2.90 十亿的 CAGR 增长（来
源)

准备好制定转印贴花规格了吗？ ↑

转印贴花能否成功，取决于投产前已经确定的细节：图稿是否适合单色刀刻乙烯基膜，线条是否达到经过测试的最小值，哪种膜材和胶黏剂与基材匹配，哪种转移胶带粘性与图稿相符，以及该批次必须通过哪项检验标准。这些贴花按上述条款下单，价格、生产天数以及任何性能宣称，都会在报价和样稿阶段以书面形式确认。请发送轮廓化矢量文件、成品外部尺寸以及目标表面的照片，以索取书面报价和样稿。

[1]PrintRunner：转印贴纸用途、2 mil 膜材、轻度户外评级。 ↩
[4]Decals.com：转移膜无法释放的原因。 ↩
[5]Want Stickers：底纸、乙烯基和转移膜结构。 ↩
[6]4over4：黏性与细节等级的匹配。 ↩
[7]Sticker Mule 材料常见问题：3.4 mil 白色乙烯基，侧重室内，无覆膜。 ↩ [8]The Print Reviewer：乙烯基何时优于 UV DTF。 ↩ [9]Sticker Mule 转印常见问题：尺寸、线宽、间隙和分辨率限制。 ↩ [10]Decals.com 指南：最小文字、线宽和施工温度。 ↩
[11]YG Tape：切割过浅时，小文字最先失效。 ↩
[12]Stickerit：兼容表面、油漆固化、文件格式和户外寿命。 ↩
[13]Kim's Direct：包括低表面能材料在内的剥落原因。 ↩ [14]Flywheel Brands：按膜材体系划分的户外寿命及水平面减幅。 ↩ [15]Avery Dennison MPI 1105：耐久性、施工温度和储存期。 ↩ [16]PalmGear：转移膜品牌不可互换。 ↩
[17]FINAT：剥离、初黏和尺寸稳定性测试方法。 ↩ [18]Brady：ASTM G155 测试及无依据的耐久性声明。 ↩ [19]Printable Press：异丙醇清洁和干燥时间。 ↩

[20]Vinyl Status：最低 50°F 表面温度。 ↩
[22]UL 969（ANSI）：标记和标签系统标准的适用范围。 ↩ [23]CPSC：儿童玩具和护理用品的邻苯二甲酸酯限值。 ↩ [24]OEHHA：BPS 第 65 号提案列名及警示日期。 ↩ [25]FINAT PFAS 说明：食品接触包装的 PPWR PFAS 限制。 ↩

Product Option